

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

Advertisement for Bids

Sealed proposals for the **Third Street Reconstruction Project (Clay Pavers)**, will be received by the Village of New Albany, Franklin County, Ohio, Village Hall, 99 W. Main Street, New Albany, Ohio until 11:30 A.M., local time on:

August 30, 2010

and at that time and place will be publicly opened and read aloud. All bids will be considered valid until 60 days after the opening date, although not accepted or rejected.

Roadway: 13,501 square feet of permeable clay pavers. Permeable clay pavers shall be:

- A Grade pavers manufactured/supplied by a member of the Brick Institute of America (BIA)
- The Basis-of-Design shall establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products.
- Basis-of-Design for the permeable clay paver units shall be StormPave by Pine Hall Brick.
 - Paver Type: Solid, rectangular clay brick pavers with lugs for permeable rainwater application
 - Color: Basis-of-Design color shall be “Ironspot” by Pine Hall Brick
 - Size: 4 inches x 8 inches x 2-3/4 inches thick
 - Edge: Chamfered
 - Joint Size: 1/2 inch maximum
- Pavers shall meet the following requirements set forth in ASTM C 1272 specifications for heavy vehicular paving brick and shall conform to the PX application.
 - Minimum average compressive strength of 10,000 psi.

- The average cold water absorption shall not be greater than 6% with no individual unit testing greater than 7%. Absorption test results may not be achieved through the use of sealers or other products applied to the clay paver.
- Resistance of 50 freeze-thaw cycles, when tested in accordance with ASTM C67. In addition the clay paver must pass CSAA231.2 freeze thaw test in saline solution without the use of sealers or other products applied to the paver. A test report must be submitted by the manufacturer.
- Dimensional tolerances shall meet the PX standard. In addition, the dimensional tolerances around the mean values for length, width, and depth shall be 1/16".
- The pavers shall be solid units without core holes or other perforations.
- Submit statement to certify that the manufacturer conducts a test sampling of 24 pavers for every 50,000 pavers manufactured to determine the pavers compliance with dimensional and water absorption characteristics. The 24 paver samples shall be representative of the color mix in the typical finished package and chosen on a consistent basis from one kiln car.

Material cost estimate is **\$65,345.00**.

Sidewalk: 5,603 square feet of clay pavers. Clay pavers shall be:

- A Grade pavers manufactured/supplied by a member of the Brick Institute of America (BIA)
- The Basis-of-Design shall establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products.
- Basis-of-Design for the clay paver units shall be shall be English Edge by Pine Hall Brick.
 - Paver Type: Solid, rectangular clay brick pavers
 - Color: Basis-of-Design color shall be "Full Range" by Pine Hall Brick
 - Size: 4 inches x 8 inches x 2-1/4 inches thick, including spacer nibs on sides
 - Edge: Straight

- Pavers shall meet the following requirements set forth in ASTM C 902 specifications for light-traffic paving brick and shall conform to class SX, Type 1, PX application.
 - Minimum average compressive strength of 10,000 psi.
 - The average cold water absorption shall not be greater than 6% with no individual unit testing greater than 7%.
Absorption test results may not be achieved through the use of sealers or other products applied to the clay paver.
 - Resistance of 50 freeze-thaw cycles, when tested in accordance with ASTM C67. In addition the clay paver must pass CSAA231.2 freeze thaw test in saline solution without the use of sealers or other products applied to the paver. A test report must be submitted by the manufacturer.
 - Dimensional tolerances shall meet the PX standard. In addition, the dimensional tolerances around the mean values for length, width, and depth shall be 1/16".
 - The pavers shall be solid units without core holes or other perforations.
 - Submit statement to certify that the manufacturer conducts a test sampling of 24 pavers for every 50,000 pavers manufactured to determine the pavers compliance with dimensional and water absorption characteristics. The 24 paver samples shall be representative of the color mix in the typical finished package and chosen on a consistent basis from one kiln car.

Material cost estimate is **\$16,809.00**.

The work for which proposals are invited consists of furnishing of all materials by September 20, 2010.

Copies of the Contract Documents and Specifications are on file with the receptionist, 99 W. Main Street, New Albany, Ohio, where they are available for inspection by prospective bidders. All proposals shall be made on standard bidding blanks furnished by the Village of New Albany. The envelope containing the proposal shall be endorsed with pertinent description of the work bid upon. Contract Documents and Specifications may be obtained from the above office upon payment of \$10.00 per set, which amount will not be refunded. Please make checks payable to Village of New Albany.

Each bid shall be signed by a corporate officer of the bidder, if bidder is a corporation, and shall contain the full name and address of each person or company interested in the same. A Contract Bond (100% of award amount) with a satisfactory surety company, conditioned according to the law, will be required for the faithful performance of the Contract.

Each bidder must insure that all employees and applicants for employment are not discriminated against because of race, color, religion, sex, or national origin.

The address of the bidder shall be given with the signature of the bid. The Bidder is required to fill out and where required execute each of the documents outlined in the Information for Bidders section.

The notice of award will be sent to the lowest and best bidder by **September 1, 2010**. A Contract will be entered into within 10 days after the notice of award has been executed.

The contract and notice to proceed shall be signed on or about **September 8, 2010**.

The Bidder will be required to state in full detail, with his proposal, his experience in this class of work; bids from Contractors inexperienced in this particular class of work will not be considered.

The Contractor shall, to the extent possible, use, and shall cause all of his Subcontractors to use, Ohio products, materials, services, and labor in connection with the Project.

Village of New Albany, Franklin County, Ohio, reserves the right to reject any or all bids, including all bids, which, in the opinion of the Village Engineer, show evidence of unbalancing prices, and also to waive technical defects as the interest of Village of New Albany may require.

Joseph Stefanov
Administrator
New Albany, Ohio

PUBLISH: **August 12, 2010**
August 19, 2010

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

**Specifications for
Third Street Reconstruction Project (Clay Pavers)**

August 30th, 2010

It is the intent of these specifications to describe the type and quality of clay pavers required by the Village of New Albany for use in the Third Street Reconstruction Project. This bid shall not intentionally exclude any bidder from receiving full consideration due to minor errors or differences.

The following shall be bid separately:

- **Roadway:** 13,501 square feet of permeable clay pavers
- **Sidewalk:** 5,603 square feet of clay pavers

Instructions: Please place an “X” in the right hand column to signify that this product meets or exceeds those specifications outlined below.

ROADWAY		
Item No.	Minimum Specification	Meets/Exceeds Specification
1.	A Grade pavers manufactured/supplied by a member of the Brick Institute of America (BIA).	
2.	The Basis-of-Design shall establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products.	
3.	Basis-of-Design for the permeable clay paver units shall be StormPave by Pine Hall Brick. <ul style="list-style-type: none"> ▪ Paver type: Solid, rectangular clay brick pavers with lugs for permeable rainwater application ▪ Color: Basis-of-Design shall be “Ironspot” by Pine Hall Brick ▪ Edge: Chamfered ▪ Joint Size: ½ inch maximum 	

4.	<p>Pavers shall meet the following requirements set forth in ASTM C 1272 specifications for heavy vehicular paving brick and shall conform to the PX application.</p> <ul style="list-style-type: none"> ▪ Minimum average compressive strength of 10,000 psi. ▪ The average cold water absorption shall not be greater than 6% with no individual unit testing greater than 7%. Absorption test results may not be achieved through the use of sealers or other products applied to the clay paver. ▪ Resistance of 50 freeze-thaw cycles, when tested in accordance with ASTM C67. In addition the clay pavers must pass CSAA231.2 freeze thaw test in saline solution without the use of sealers or other products applied to the paver. A test report must be submitted by the manufacturer. ▪ Dimensional tolerances shall meet the PX application. In addition, the dimensional tolerances around the mean values for length, width, and depth shall be 1/16”. ▪ The pavers shall be solid units without core holes or other perforations. ▪ Submit statement to certify that the manufacturer conducts a test sampling of 24 pavers for every 50,000 pavers manufactured to determine the pavers compliance with dimensional and water absorption characteristics. The 24 paver samples shall be representative of the color mix in the typical finished package and chosen on a consistent basis from one kiln car. 	
----	---	--

SIDEWALK		
Item No.	Minimum Specification	Meets/Exceeds Specification
1.	A Grade pavers manufactured/supplied by a member of the Brick Institute of America (BIA).	
2.	The Basis-of-Design shall establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance, and other characteristics for purposes of evaluating comparable products.	

3.	<p>Basis-of-Design for the clay paver units shall be English Edge by Pine Hall Brick.</p> <ul style="list-style-type: none"> ▪ Paver type: Solid, rectangular clay brick pavers ▪ Color: Basis-of-Design shall be “Full Range” by Pine Hall Brick ▪ Edge: Straight ▪ Size: 4 inches x 8 inches x 2¼ inches thick, including spacer nibs on sides 	
4.	<p>Pavers shall meet the following requirements set forth in ASTM C 902 specifications for light-traffic paving brick and shall conform to class SX, Type 1, PX applications.</p> <ul style="list-style-type: none"> ▪ Minimum average compressive strength of 10,000 psi. ▪ The average cold water absorption shall not be greater than 6% with no individual unit testing greater than 7%. Absorption test results may not be achieved through the use of sealers or other products applied to the clay paver. ▪ Resistance of 50 freeze-thaw cycles, when tested in accordance with ASTM C67. In addition the clay pavers must pass CSAA231.2 freeze thaw test in saline solution without the use of sealers or other products applied to the paver. A test report must be submitted by the manufacturer. ▪ Dimensional tolerances shall meet the PX application. In addition, the dimensional tolerances around the mean values for length, width, and depth shall be 1/16”. ▪ The pavers shall be solid units without core holes or other perforations. ▪ Submit statement to certify that the manufacturer conducts a test sampling of 24 pavers for every 50,000 pavers manufactured to determine the pavers compliance with dimensional and water absorption characteristics. The 24 paver samples shall be representative of the color mix in the typical finished package and chosen on a consistent basis from one kiln car. 	

Bidders are required to submit with their bids, the latest literature that fully describes the material being bid and to complete the above verification of compliance with the material specifications. Should a bidder fail to submit the literature and verify specification requirements, the bid will not be considered. Failure to meet both requirements shall be just cause to consider the bid non-responsive.

Bids varying from the above specifications must clearly indicate points of variance.

Bids shall be submitted on the attached bid form (Page 5)

The Village of New Albany will consider performance history of material, vendor's service, and vendor's overall responsiveness when evaluating bids.

Materials purchased are to be promptly delivered to the PURCHASING AGENT of the Village of New Albany, Ohio, by **September 20, 2010**.

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

Bid Form

Roadway	Price
13,501 square feet of permeable clay pavers	
Sidewalk	Price
5,603 square feet of clay pavers	

Company Name: _____

Address: _____

Date: _____

Phone: _____

Title: _____

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

Personal Property Tax Affidavit

State of: _____

County of: _____

BID Identification: _____

CONTRACTOR _____, being first duly sworn, deposes and says that he is _____ (sole owner, a partner, president, secretary, etc.) of _____, the party making the foregoing bid, and that he was/was not charged (indicate one) at the time the bid was submitted with any delinquent personal property taxes on the general tax list of personal property of any county in which the Village of New Albany has territory. If the party affirms that he was charged with delinquent personal property taxes on any such tax list, he shall set forth below the amount of such unpaid delinquent taxes due, along with any unpaid penalties and interest thereon.

Delinquent personal property taxes due and unpaid..... \$ _____
Penalties and interest due and unpaid..... \$ _____
Total amount due and unpaid..... \$ _____

Signed: _____

Subscribed and sworn to before me this _____ day of _____, 2010.

Seal of Notary _____

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

Notice of Award

TO: _____

FROM: _____

Project: **Third Street Reconstruction Project (Clay Pavers)**
 for the Village of New Albany, New Albany, Ohio

The Owner has considered the Bid submitted by you for the above described material in response to the Legal Notice dated September 12th and 19th.

You are hereby notified that your proposal has been accepted for items in the amount of \$ _____.

You are required to execute this Contract and return the original copy within ten (10) calendar days from the date of this notice to you.

If you fail to execute said Contract within ten (10) days from the date of this notice, said Owner will be entitled to consider all your right arising out of the Owner's acceptance of your Proposal as abandoned. The Owner will be entitled to such other rights as may be granted by Law.

You are required to return an acknowledged copy of this Notice of Award to the Owner.

Dated this _____ of _____, 2010.

By: _____
Title: Village Administrator

ACCEPTANCE OF NOTICE

Receipt of the above Notice of Award is hereby acknowledged.

Contractor: _____

This day of _____ of _____, 2010.

By: _____

Title: _____

**VILLAGE OF NEW ALBANY
DEPARTMENT OF PUBLIC SERVICE**

Non-Collusion Affidavit

State of: _____

County of: _____

Project Name: _____

Project Number: _____

BID Identification: _____

CONTRACTOR _____, being first duly sworn, deposes and says that he is _____ of _____, (sole owner, a partner, president, secretary, etc.) the party making the foregoing Bid; that such Bid is not made in the interest of or on behalf of any undisclosed person, partnership, company, association, organization, or corporation; that such bid is genuine and not collusive or sham; that said Bidder has not directly or indirectly induced or solicited any other Bidder to put in a false or sham Bid, and has not directly or indirectly colluded, conspired, connived, or agreed with any Bidder or anyone else to put in a sham Bid, or that anyone shall refrain from bidding; that said Bidder has not in any manner, directly or indirectly, sought by agreement, communication or conference with anyone to fix the Bid price of said Bidder or of any other Bidder, or to fix any overhead, profit, or cost element of such Bid price, or of that of any other Bidder, or to secure any advantage against the owner awarding the contract or anyone interested in the proposed contract; that all statements contained in such Bid are true; and, further, that said Bidder has not, directly or indirectly, submitted his bid price or any breakdown thereof, or the contents thereof, or divulged information or data relative thereto, or paid and will not pay any fee in connection therewith, to any corporation, partnership, company, association, organization, Bid depository, or to any member or agent thereof, or to any other individual except to such person or persons as have a partnership or the financial interest with said Bidder in his general business.

Signed:

Contractor

Title

Subscribed and sworn to before me this _____ day of _____, 2010.

Seal of Notary: _____